

KAIKA

_ Stufa a pellet di dimensioni ridotte, realizzata in alluminio verniciato a polveri; disponibile nei colori: white, red, black, aluminium.

_ Small pellet stove, made of powder coated aluminum, available in the following colours: white, red, black, aluminum.

_ Poêle à pellet de dimensions réduites, réalisé en aluminium peint avec des poudres; disponible dans les coloris: white, red, black, aluminium.

_ Pelletheizofen mit reduzierten Abmessungen, aus pulverlackiertem Aluminium; in den Farben white, red, black und aluminium lieferbar.

_ Estufa de pellets de reducido tamaño, realizada en aluminio pintado con polvo; disponible en los colores: white, red, black, aluminium.



AIR 6 / OYSTER 6 p.68



KAIKA / KAIKA OYSTER




	AIR	OYSTER
POWER max	6 - 5.160 [kW-kcal/h]	5,4 - 4.644 [kW-kcal/h]
POWER min	2 - 1.720 [kW-kcal/h]	2,3 - 1.978 [kW-kcal/h]
	91,1 [%]	93,4 [%]
	20 [l]	20 [l]
	pellet Ø 6-8 x 5÷30 [mm]	pellet Ø 6-8 x 5÷30 [mm]
	~ 0,5 / ~ 1,45 [kg/h]	~ 0,5 / ~ 1,2 [kg/h]
	~ 20 / ~ 7 [h]	~ 25 / ~ 11 [h]
	129/40 - 147/35 - 172/30 [m³]	116/40 - 133/35 - 155/30 [m³]
	8 [cm]	8 [cm]
	120 [kg]	120 [kg]
	10 - 0,10 [Pa- mbar]	10 - 0,10 [Pa- mbar]
	170 [°C]	115 [°C]
	min. 4 - max 6 [g/s]	min. 2,8 - max 3,8 [g/s]



EN 14785
BlmSchV
ART. 15a B-VG
REGENSBURGER / MÜNCHENER BStB
BAFA gefördert



302_White



108_Red



303_Black



315_Aluminium



FACE



POWER max	6 - 5.160 [kW-kcal/h]
POWER min	2 - 1.720 [kW-kcal/h]
	89,1 [%]
	20 [l]
	pellet Ø 6-8 x 5÷30 [mm]
	~ 0,5 / ~ 1,45 [kg/h]
	~ 20 / ~ 7 [h]
	129/40 - 147/35 - 172/30 [m³]
	8 [cm]
	120 [kg]
	10 - 0,10 [Pa- mbar]
	170 [°C]
	min. 4 - max 6 [g/s]



EN 14785
BlmSchV
ART. 15a B-VG
REGENSBURGER / MÜNCHENER BStB
BAFA gefördert



304_Bordeaux



308_Dark



313_Silver



NASIK



	AIR
POWER max	7 - 6.020 [kW-kcal/h]
POWER min	2,4 - 2.064 [kW-kcal/h]
	89,1 [%]
	18 [l]
	pellet Ø 6-8 x 5÷30 [mm]
	~ 0,6 / ~ 1,6 [kg/h]
	~ 15 / ~ 6,5 [h]
	151/40 - 172/35 - 201/30 [m³]
	8 [cm]
	130 [kg]
	10 - 0,10 [Pa- mbar]
	170 [°C]
	min. 4 - max 6 [g/s]




EN 14785
BlmSchV
ART. 15a B-VG
REGENSBURGER / MÜNCHENER BStB
BAFA gefördert



402_Rovere



401_Laccato bianco



KAMA



	AIR
POWER max	7 - 6.020 [kW-kcal/h]
POWER min	2,4 - 2.064 [kW-kcal/h]
	89,1 [%]
	18 [l]
	pellet Ø 6-8 x 5÷30 [mm]
	~ 0,6 / ~ 1,6 [kg/h]
	~ 15 / ~ 6,5 [h]
	151/40 - 172/35 - 201/30 [m³]
	8 [cm]
	130 [kg]
	10 - 0,10 [Pa- mbar]
	170 [°C]
	min. 4 - max 6 [g/s]



EN 14785
BlmSchV
ART. 15a B-VG
REGENSBURGER / MÜNCHENER BStB
BAFA gefördert

